Material Safety Data Sheet

Industrie- en Handelsonderneming Superstar B.V. 02/06/16

1. Chemical product and company identification.

Description: BODYPAINT

Product type: Past cake type paints Application: colourful on body

Manufacturer,

Company name: Superstar B.V.

Company address: Florijnstraat 12, 4903 RM, Oosterhout, The Netherlands

Telephone: +31162457400

Poison control centre: Tel. +3109000388 (The Netherlands)

2. Composition, information on ingredients.

Ingredients: Glycerin, Kaolin, Polysorbate 20, Talc, Zincstearate, Aqua, Polysorbate 80, Cetyl Acetate, Stearyl Acetate, Oleyl Acetate, Acetylated Lanolin Alcohol, Magnesium Aluminium Silicate, Magnesium Carbonate, Sodium Laureth Sulphate, Xanthan Gum, Sodium Citrate, Phenoxyethanol, Sodiumhydroxymethylglycinate, Polyethylene Terephthalate, C.I. 77891, 15800, 74160, 74260, 11680, 12490, 12085, 77492, mica 77019.

3. Hazards identification.

3.1 HMIS Rating.

4 = Severe

3 = Serious

2 = Moderate

1 = Slight

0 = Minimal

Health = 0 Flammability = 0 Reactivity = 0

3.2 Potential Health Effects.

Immediate hazards.

INGESTION: No hazards known INHALATION: No hazards known SKIN: No hazards known EYES: No hazards known

Delayed hazards.

No hazards known

4. First Aid Measures.

INGESTION: Not expected to require first aid measures. If large amounts are swallowed, give

water to drink and get medical advice.

INHALATION: Remove to fresh air. Seek medical attention for any breathing difficulties.

SKIN: Wash the skin with soap and water.

EYES: Immediately flush eyes with plenty of water.

5. Fire Fighting Measures.

Auto –ignition Temperature: Not available Upper / Lower Flammable limits: Not available Upper / Lower Explosive limits: Not available Flash Point: >150°C
Will not burn unless: >250°C

Suitable Extinguishing Media: Carbon Dioxide, Powders, Water Spray

6. Accidental Release Measures.

Protective Measures: Children under 6 years should use with adult supervision.

7. Handling and Storage.

7.1 Handling.

Handle in accordance with good industrial hygiene and safety practices.

7.2 Storage.

Store in a cool, dry place.

8. Exposure Controls / Personal Protection.

8.1 Exposure Controls.

No specific control measures necessary under normal conditions of use.

8.2 Personal Protection.

No special protection necessary.

8.3 Exposure Guidelines.

None established.

9. Physical and Chemical Properties.

Percent Volatiles <3% Water
Ph @ 20 -----Specific Gravity 1.70± 0.30g/ml
Appearance colours solid
Auto –Ignition Temperature Not Available
Melting Point >250°C

Vapour Density {Air = 1} Vapour Pressure hPA @ 20 N/A kg/cm Evaporation Rate {Butyl Acetare = 1} Not Available Upper / Lower Explosive Limits, % by Vol. Not Available Upper / Lower Flammable Limits Not Available Flash Point >150°C **Freezing Point** Odour Mild Odour Threshold ppm Not Available Solubility in water Soluble Coefficient of Water / Oil Distribution Not Available

10. Stability and Reactivity.

Normally Stable.

Conditions to avoid:

Over exposure to water, or to wet.

Incompatibilities:

None Known,

<u>Decomposition Products may include:</u> Calcium Oxide, Water, Carbon Dioxide

Hazardous Polymerization:

Will not occur.

Other Hazards:

None Known.

11. Toxicological Information.

There is no data available on the preparation itself.

12. Ecological Information.

There is no data available on the preparation itself.

13. Disposal Consideration.

Dispose of according to Local, State / Provincial and Federal requirements.

14. Transport Information.

14.1 US: Department of Transportation. (DOT)

The data provided in the section is for information only and may not be specific for your package size. You will need to apply to the appropriate regulators to properly classify your shipment for transportation. NOT REGULATED

14.2 Canadian Transportation of Dangerous Goods.

NOT REGULATED

15. Regulatory Information (Selected Regulations).

15.1 US Federal Regulation.

These paint product CONFORMS to the health requirements of ASTM D-4236. These products must bear the following statement "Conforms to ASTM D-4236".

15.2 These paint products conform to EU 76/768/EEC, and CE EN – 71



